



PART NUMBER:
MCEEB - * * * T - 1 1 1 * *

SERIES — * * *
 NO. OF POS. — T
 REF. TABLE — 1 1 1
 CONTACT PLATED OPTION — * *
 1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD

HOUSING COLOR OPTION
 BLANK: BLACK
 W: WHITE

"F" LENGTH OPTION
 1: 2.30mm
 2: 2.54mm
 3: 3.10mm

TRAY PACKAGE

TIN PLATING ON SOLDER TAIL

MATERIALS
 HOUSING: THERMOPLASTIC (UL 94V-0)
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION
 CURRENT RATING: 1.1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+105°C

TABLE

DIMENSIONS					
POS.	A	B	C	D	E
036	25.00	9.15	7.65	6.00	8.15
064	39.00	23.15	21.65	20.00	22.15
098	56.00	40.15	38.65	37.00	39.15
164	89.00	73.15	71.65	70.00	72.15



TOLERANCES
 X.±0.40 .XX±0.20
 .X±0.30 .XXX±0.10

REV.	A	DRAWN BY	Zhong 2017/12/5	TITLE	PCI EXPRESS, 1.00mm PITCH, PCB MOUNT, VERTICAL, FEMALE, 1 KEY, WITH POST				
		APPROVED BY	Lion 2017/12/5	DRAW NO.	MCEEB-001	UNIT	MM	Sheet	1/1