



MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0)
 SHELL: SPCC, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 1 AMP MAX
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+85°C

PART NUMBER:

BUSAL - 0 4 * T - 1 2 2

SERIES — NO. OF POS. — CONTACT PLATED OPTION — TIN PLATING ON SOLDER TAIL — TAPE REEL PACKAGE

- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	Zhong 2018/5/16	TITLE	USB A TYPE, PCB MID MOUNT, REVERSE TYPE, R/A, METAL SHIELD, FEMALE				
		APPROVED BY	Lion 2018/5/16	DRAW NO.	BUSAL-002	UNIT	MM	Sheet	1/1

BUSAL-002	UNIT	MM	Sheet	1/1
-----------	------	----	-------	-----