

OPEN TYPE

MATERIALS

HOUSING: THERMOPLASTIC (UL 94V-0)
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA
 TIN PLATING ON SOLDER TAIL

SPECIFICATION

CURRENT RATING: 2 AMP MAX
 DIELECTRIC WITHSTANDING: 250V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 500M OHMS MIN AT DC 100V
 OPERATION TEMPERATURE: -40°C~+105°C

PART NUMBER:

AMJAA - 0 2 * - 1 4 1 *

SERIES

NO. OF POS.

CONTACT PLATED OPTION


- 1: GOLD FLASH
- 3: 3u" GOLD
- 5: 5u" GOLD
- 6: 10u" GOLD
- 7: 15u" GOLD
- 9: 30u" GOLD
- N: NICKEL

HOUSING COLOR OPTION
 BLANK: BLACK
 W: WHITE
 Y: YELLOW
 R: RED

BAG PACKAGE



| TOLERANCES | |
|------------|-----------|
| X.±0.40 | .XX±0.20 |
| .X±0.30 | .XXX±0.10 |



REV. A
 DRAWN BY Zhong 2018/7/20
 APPROVED BY Lion 2018/7/20

| TITLE | MINI JUMPER 2.54mm | | | | |
|----------|--------------------|------|----|-------|-----|
| DRAW NO. | AMJAA-001 | UNIT | MM | Sheet | 1/1 |