



**MATERIALS**

HOUSING: THERMOPLASTIC (UL 94V-0)  
 INSULATOR: POM (UL 94V-0)  
 SHELL: ZINC, NICKEL PLATING  
 POST: COPPER ALLOY, TIN PLATING  
 TERMINAL: COPPER ALLOY, GOLD PLATED ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL  
 WASHER: IRON, NICKEL PLATING  
 NUT: ZINC, NICKEL PLATING

**SPECIFICATION**

FREQUENCY RANGE: DC-4 GHz  
 VSWR: 1.30 MAX.  
 OPERATION TEMPERATURE: -40°C~+105°C

**PART NUMBER:**

RBND E - \* \* T 1 - 1 \* 3 \*

SERIES

∅A DIM. & OHM OPTION  
 REF. TABLE  
 5: 50 OHM  
 7: 75 OHM

HOUSING COLOR OPTION  
 BLANK: BLACK  
 W: WHITE

PACKAGE OPTION  
 1: TRAY  
 4: BAG

CONTACT PLATED OPTION

1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 6: 10u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD

TIN PLATING ON SOLDER TAIL

**TABLE**

| ∅A   | IMPEDANCE |
|------|-----------|
| 4.60 | 50 OHM    |
| 3.00 | 75 OHM    |