

P.C.B. LAYOUT
TOP VIEW ±0.05

MATERIALS

INSULATOR: POM (UL 94V-0), WHITE
 BODY: COPPER ALLOY, NICKEL PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATING

SPECIFICATION

VOLTAGE RATING: 500V AC
 IMPEDANCE: 50 OR 75 OHM
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 INSULATION RESISTANCE: 5000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+155°C

PART NUMBER:

RBNCA - * * 1 - 1 * 1

SERIES

OHM OPTION
 5: 50 OHM
 7: 75 OHM

PACKAGE OPTION
 1: TRAY
 4: BAG

CONTACT PLATED OPTION
 1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10


REV.

A

DRAWN BY Zhong 2019/1/11

TITLE

BNC, PCB MOUNT, R/A, FEMALE



APPROVED BY Lion 2019/1/11

DRAW NO.

RBNCA-001

UNIT

MM

Sheet

1/1