



CAP

PART NUMBER:  
 ABTDK - 0 3 \* - 1 2 1

SERIES ————  
 NO. OF POS. ————  
 CONTACT PLATED OPTION ————

TAPE REEL PACKAGE (WITH CAP)

- CONTACT PLATED OPTION
- 1: GOLD FLASH
  - 3: 3u" GOLD
  - 5: 5u" GOLD
  - 6: 10u" GOLD
  - 7: 15u" GOLD
  - 9: 30u" GOLD

**MATERIALS**

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
 CAP: HI-TEMP. PLASTIC (UL 94V-0), BLACK  
 TERMINAL: COPPER ALLOY, GOLD PLATED

**SPECIFICATION**

CURRENT RATING: 3 AMP MAX  
 VOLTAGE RATING: 15V MAX  
 DIELECTRIC WITHSTANDING: 350V AC FOR ONE MINUTE  
 INSULATION RESISTANCE: 1000M OHMS MIN AT DC 250V  
 OPERATION TEMPERATURE: -40°C~+85°C



TOLERANCES  
 X.±0.40 .XX±0.20  
 .X±0.30 .XXX±0.10

|      |   |             |                |          |   |      |    |       |     |
|------|---|-------------|----------------|----------|---|------|----|-------|-----|
| REV. | A | DRAWN BY    | Zhong 2020/3/6 | TITLE    | BATTERY, 3.00mm PITCH, PCB MOUNT, VERTICAL SMT, WITH POST, FEMALE |      |    |       |     |
|      |   | APPROVED BY | Lion 2020/3/6  | DRAW NO. | ABTDK-001   | UNIT | MM | Sheet | 1/1 |