



**MATERIALS**

HOUSING: LCP (UL 94V-0), BLACK  
 SHELL: SPCC  
 TERMINAL: COPPER ALLOY, GOLD PLATING ON CONTACT AREA  
 TIN PLATING ON SOLDER TAIL

**SPECIFICATION**

CURRENT RATING: 0.5 AMP MAX  
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE  
 CONTACT RESISTANCE: 30m OHMS MAX  
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 100V  
 OPERATION TEMPERATURE: -40°C~+85°C

**PART NUMBER:**

BDPAS - 2 0 \* T \* - 1 1 5

SERIES: BDPAS  
 NO. OF POS.: 20  
 CONTACT PLATED OPTION: \* (1-9)  
 T: TRAY PACKAGE  
 \* (1-5): SHELL PLATED OPTION  
 1: GOLD FLASH  
 3: 3u" GOLD  
 5: 5u" GOLD  
 6: 10u" GOLD  
 7: 15u" GOLD  
 9: 30u" GOLD  
 - 1: BLANK: NICKEL  
 - 1: G: GOLD  
 5: TIN PLATING ON SOLDER TAIL