



MATERIALS

INSULATOR: POM (UL 94V-0), WHITE
 HOUSING: PA66 (UL 94V-0), BLACK
 SHELL: SPCC, NICKEL PLATING
 BARREL: ZINC, NICKEL PLATING
 CENTER TERMINAL: SPCC, NICKEL PLATING
 GROUND TERMINAL: SPCC, NICKEL PLATING

SPECIFICATION

VOLTAGE RATING: 500V AC
 DIELECTRIC WITHSTANDING: 500V AC FOR ONE MINUTE
 INSULATION RESISTANCE: 5000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: $-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$

PART NUMBER:

RBNCA - * N 1 - 1 * 3

SERIES ————
 OHM OPTION ————
 5: 50 OHM
 7: 75 OHM
 PACKAGE OPTION
 1: TRAY
 4: BAG
 NICKEL PLATING ON TERMINAL



TOLERANCES	
X. ± 0.40	.XX ± 0.20
.X ± 0.30	.XXX ± 0.10

REV.	A	DRAWN BY	Kiki 2022/4/19	TITLE	BNC JACK, PCB MOUNT, R/A WITH METAL SHIELD				
		APPROVED BY	Lion 2022/4/19	DRAW NO.	RBNCA-003	UNIT	MM	Sheet	1/1

DRAW NO.	RBNCA-003	UNIT	MM	Sheet	1/1
----------	-----------	------	----	-------	-----