



MATERIALS

HOUSING: POM (UL 94V-0), WHITE
 SHELL: COPPER ALLOY, NICKEL PLATING
 CONTACT TERMINAL: COPPER ALLOY, GOLD PLATED
 SOLDER TERMINAL: COPPER ALLOY, TIN PLATING
 WASHER: SPCC, NICKEL PLATING
 HEX NUT: SPCC, NICKEL PLATING

SPECIFICATION

WORKING FREQUENCY: DC ~ 4 GHz
 DIELECTRIC WITHSTANDING: 1500V AC FOR ONE MINUTE
 INSULATION RESISTANCE: 5000M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -55°C~+125°C

PART NUMBER:

RBNAC - * * 7 - 1 * 1

SERIES —
 OHM OPTION —
 5: 50 OHM
 7: 75 OHM
 PACKAGE OPTION —
 1: TRAY
 4: BAG

CONTACT PLATED OPTION

1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 6: 10u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	SIMON 2020/4/22	TITLE	BNC, SOLDER MOUNT, VERTICAL WITH BULKHEAD, FEMALE				
		APPROVED BY	Lion 2020/4/22	DRAW NO.	RBNAC-001	UNIT	MM	Sheet	1/1