


MATERIALS

HOUSING: HI-TEMP. PLASTIC (UL 94V-0), BLACK
 SHELL: COPPER ALLOY, TIN PLATING
 TERMINAL: COPPER ALLOY, GOLD PLATING

SPECIFICATION

CURRENT RATING: 1.8 AMP MAX (ONLY PIN 1, 5), OTHER 1 AMP MAX
 DIELECTRIC WITHSTANDING: 100V AC FOR ONE MINUTE
 CONTACT RESISTANCE: 30m OHMS MAX
 INSULATION RESISTANCE: 100M OHMS MIN AT DC 500V
 OPERATION TEMPERATURE: -40°C~+105°C



**P.C.B LAYOUT
 TOP VIEW ±0.05**

PART NUMBER:
BUSTB - 0 5 * - 1 2 L *

SERIES ————
 NO. OF POS. ————
 CONTACT PLATED OPTION ————

POST OPTION
 BLANK: W/O POST
 P: WITH POST

TAPE REEL PACKAGE

1: GOLD FLASH
 3: 3u" GOLD
 5: 5u" GOLD
 7: 15u" GOLD
 9: 30u" GOLD



TOLERANCES	
X.±0.40	.XX±0.20
.X±0.30	.XXX±0.10

REV.	A	DRAWN BY	Kiki 2022/3/24	TITLE	MICRO USB B TYPE, PCB MOUNT, SMT, METAL SHIELD, WITH POST, FEMALE				
		APPROVED BY	Lion 2022/3/24	DRAW NO.	BUSTB-020	UNIT	MM	Sheet	1/1